

PRODUCT SPECIFICATION CENTRAL BOLLARD

Patented GB2299967B



The Central Bollard utilises the most up-to-date blow moulded technology which leaves the Bollard with a non-porous, smooth and easy clean surface without the need for a special anti-grime application that can deplete quite rapidly with today's cleaning methods/products. With its special patented graphic process, this bollard boasts a 10 year

MATERIAL

- ❑ Mold in graphics guaranteed for 10 years against peeling or fading
- ❑ Blow Moulded Low density polythene material –(UV stabilised) 5mm
- ❑ Radius top design to aid impact recovery and reduce corner tears
- ❑ 4 Equal Sides any or all of which can display a DTp symbol/or yellow panel
- ❑ Full length yellow side panels
- ❑ 4 retroreflective disks applied to the recesses around the Aspect face
- ❑ Conforms to prescribed luminance performance as set out BS873
- ❑ Date of manufactured stamped
- ❑ Inter-changeable with other standard industry baselights
- ❑ Fully translucent
- ❑ Flexible or Rigid option

BASE FRAME

- ❑ Full 3mm galvanised steel frame which fits into base plinth
- ❑ 3 point Steel rivets per side
- ❑ Pre drilled to accept shear pins or M8 bolts for bollard attachment

FINISH

- ❑ High profile black outline available as optional extra
- ❑ Moulded in recess to accept 4 x Class 1 reflective disks
- ❑ Available for non-lit bases in 3M VIP Diamond Grade (12 year guarantee) or Class 1 (10 year guarantee)

Useful Codes:	Keep Left	D610
	Keep Right	D610R
	No Entry	D616
	Turn Left	D606
	Turn Right	D606R
	Pass Either Side	D611
	Cycles Only	D955