


 11W | TC | G23 |
  18W | TCL | 2G11 |
 IP65 | EN 60598 |
 
 | 10 joules | 850° hot wire (30 sec) |
 

A robust bulkhead using low energy fluorescent lamps with the emphasis on a smooth appearance.

The construction is simple with a high degree of engineering and special attention has been paid to maintenance and safety aspects.



- Strong die cast aluminium body with rounded profile
- Clear polycarbonate diffuser fixes via two cross head screws
- IP65 rated, with silicone gasket seal
- Gloss white stove enamelled gear-tray doubles as reflector
- Double pole automatic isolation
- 3 pole terminal block with built-in fuse
- Threaded holes with white cap for 20mm side entry



Materials/Finish


Body: Die-cast aluminium, painted white with gloss white stove enamelled gear-tray. Stainless steel lamp support. Diffuser: Clear UV stabilized prismatic polycarbonate.

Installation/Mounting

Direct wall or ceiling mounting. 4 fixing points. Knockouts and pre-drilling points for BESA box fixing. Threaded holes with white cap for 20mm side entry through wiring. Hinged gear-tray provides quick access to 3 pole terminal block with built-in fuse. Double pole automatic isolation. Gear-tray secures with single screw. Safety-cord between body and diffuser.

Specification

To specify state: IP65 vandal resistant bulkhead with die-cast aluminium body and clear polycarbonate diffuser for 1 x 18W/2 x 11W compact fluorescent lamps with internal fuse and automatic disconnection, plus diffuser retaining safety cord. As Thorn Dragon.



Ordering Guide

Supplied complete with lamp(s).

Lamp type & rating	Description (kg)	Weight	Cat. No.
TC 2 x 11W	Dragon with switchstart (HPF) control gear	1.2	OBD2011
TCL 1 x 18W	Dragon with high frequency control gear	1.1	OBDZ1018

Export voltages available, refer to page 553 for details.