

PRODUCT SPECIFICATION EXLITE DELTA - IP rating **IP65**



BODY CASING & LID COMPONENTS

- ❑ A Type Lantern Manufactured from LM6-M Cast Aluminium in accordance with BS873, Part 5 Section 4.2.1 (e), (f) and (g).
- ❑ Two piece body, incorporating sealed Photocell aperture on upper surface
- ❑ 3mm UV Stabilised Foam Gasket Seal
- ❑ High Impact 4mm UV stabilised Polycarbonate Lens secured into lid of Sign Body
- ❑ Lower Single Fixing Point (M8x20)
- ❑ All fixings Stainless Steel bushed

EXTERNAL FINISH

- ❑ Pre-treated Powder Coated to customer specification - other colours available

GEAR TRAY – 3 Year Guarantee

- ❑ All units independently fused fluorescent circuits complete with power factor Correction ≥ 0.9 (lagging)
- ❑ Plug & Socket earth lead connection to body
- ❑ Internal Photo Electric Control facility
- ❑ Gear Tray configurations (also available as retrofit) options

LED 240V	1 x 11W
LED 24V AC	2 x 11W
2 x 7W	2 x 11W c/w Longlife Monitor
2 x 8W	24V AC
Remote Monitoring Units	

REFLECTOR

- ❑ Material 0.7mm Polished Aluminium
- ❑ Light Output Conforms to BS873 part 5: 1983 Mean Luminance Satisfies both categories 1 & 2

BRACKETRY – all Cast Aluminium LM6-M unless otherwise stated

- ❑ Bracketry fitted as standard (unless specified by customer)
- ❑ Single, Double Post Top Brackets from 76mm upto 89mm
- ❑ Single, Double Through Brackets from 76mm
- ❑ 89mm upto 140mm Single & Double Post Top Bracketry available Galv/Painted
- ❑ Wall Mounting Bracket (Galv/Painted)
- ❑ Tespa Bracket with anti-rotational features

SIGNATURE[®] LIMITED – Signature House, Hainge Road, Tividale, West Midlands B69 2NF
Tel: 0121 520 1016 Fax: 0121 557 0995 e-mail sales@signatureltd.com web: signatureltd.com

Signature operates a policy of continuous product development and reserves the right to improve specification without prior notice E&EO Signature 2004 – Issue 10

