



A vandal resistant wall mounted luminaire.



- Standard range for everyday use - wide choice of 70W lamp types: high pressure sodium, mercury or metal halide
- Security range - using external ignitor HPS lamps for particularly sensitive areas
- Suitable for onerous environmental conditions
- Excellent light distribution maximises spacing up to six times mounting height
- Close wall mounting resists prising off surfaces
- Photocell options

Materials/Finish

Body: Injection moulded black polycarbonate.
 Bowl: Injection moulded clear prismatic polycarbonate, hinged to body and retained by two captive tamper-resistant screws.
 Gear tray: Galvanised steel.

Installation/Mounting

Wall mountable. Cable entry via rear grommeted hole or 20mm side and top conduit entries. Recommended height 3-6m.

Specification

To specify state:
 Enclosed polycarbonate wall mounting luminaire for low wattage lamp high pressure sodium/high pressure mercury lamp with IP65 protection and vandal-resistant fixings.
 As Thorn Piazza.

Ordering Guide Supplied complete with lamp.

Lamp type & rating	Description	Weight (kg)	Cat. No.
Standard fitting			
HPS-E/I 70W	Piazza with gear and internal ignitor lamp	3.7	OS 70.4
MBF 50W	Piazza with gear	3.7	OS50.4
HPS-E/I 70W	Piazza with gear, internal ignitor lamp and photocell	3.7	OSP70.4
HIT 70W	Piazza with gear	3.7	OSSV70.4
Security fitting			
Standard HPS-T 70W	Piazza with gear	3.7	OSS 70.4
Standard HPS-T 70W	Piazza with gear and photocell	3.8	OSSP 70.4
Attachments			
Description			Cat. No.
Photocell kit for conversion to photocell operation			OSPKIT

Export voltages available, refer to page 553 for details.

