



signature signlights

Signature's level of commitment to innovation in product application is seen from both its historic and new product ranges. The use of the 2 x PL11W long life (Patent GB2287309) Monitor system offers the user a sign lantern that gives up to 4 years without lamp changes. With product guarantees from our suppliers, together with high IP ratings; maintenance and running costs are reduced dramatically. The high flux LED Delta offers up to 50,000 hours lamp life and when used with a PECU can extend to as much as 100,000 hours.

	FEATURES	PRODUCT CODES
	MAJORLITE T218™ (IP56) MAJORLITE T236™ (IP56) <ul style="list-style-type: none"> ● Side by side lantern configuration ● D and E type lanterns ● 14 SWG aluminium ● Hinged lid ● 650mm standard length arm 	MAJORLITE T218™ (IP56) ML-T218 2 x 18W Standard unit MAJORLITE T236™ (IP56) ML-LD3218 2 x 36W Standard unit PECU's available to customer specification
	MAJORLITE LD3™ (IP56) <ul style="list-style-type: none"> ● Side by side lantern configuration ● D-Type lantern ● Pressed aluminium ● Hinged lid ● 650mm standard length arm 	MAJORLITE LD3™ (IP56) ML-LD3218 2 x 18W Standard unit PECU's available to customer specification

All cast or extruded aluminium signlights and floodlights have independent lamp circuits, power correction factor ≥ 0.9 lagging. Supply, connection and Earth complies with BS4533 section 2.5. For all painted lanterns, Signature has its own paint-line and can, in addition to the standard Aircraft Grey, offer other colours to customer specification. All standard units are cleaned, primed and polyester powder coated to BS381C: 1980 - Aircraft Grey.

	OVERHEAD & UPWARDS FLOODLIGHTS (IP65) <ul style="list-style-type: none"> ● Die-cast aluminium body ● Hinged cover access ● Toughened sealed lens ● Independent lamp circuits ● Anti-vandal screen option ● 200 - 240V 50Hz 1 phase, 3 wire 	OVERHEAD & UPWARDS FLOODLIGHTS (IP65) FLO-250 2 x 250W FLO-280 2 x 280W FLO-2125 2 x 125W FLU-250 2 x 250W FLU-280 2 x 280W FLU-2125 2 x 125W
		PEDESTAL FIXING FLU-2250 2 x 250W FLU-2400 2 x 400W Standard outreach - 1200mm 2 x 125W outreach - 1800mm 76mm standard saddle bracket Galvanised steel BS729 - painted grey Optional Pedestal c/w GRP Control Box - no base post necessary - pre-wired for lower installation costs. Photocell options available - ask our sales office for assistance with 2 x 400W floodlight.