



Z5670/1/2NU Z5678/9

Lanterns for
Group B Lighting

Group B roadlighting lanterns with a cast aluminium post top mounting spigot cap. Top canopy moulded in DMC glass reinforced polyester. Non-axial dome refractor optical system with an injection moulded anti-vandal UV stabilised polycarbonate enclosing cone.

APPLICATIONS

The lantern is suitable for:

- Group B roadlighting
- All forms of amenity lighting
- Precinct lighting
- Decorative lighting

FEATURES

- Cast aluminium spigot cap.
- DMC glass reinforced polyester top canopy
- Injection moulded anti-vandal U.V. stabilised polycarbonate cone
- Non-axial asymmetric dome refractor

MATERIALS AND FINISH

Canopy: DMC glass reinforced polyester

Enclosing cone: Anti-vandal U.V. stabilised polycarbonate.

Dome refractor: Glass.

Spigot cap: Cast aluminium for 76mm dia. x 76mm high spigot.

Finish: Canopy, light grey. Spigot, silver.



LANTERN WEIGHTS AND WINDAGE DATA

Lantern Weight : Z5670/9	5.4 kg	Lantern Windage Area	0.092m ²
--------------------------	--------	----------------------	---------------------

ORDERING DATA

Z5670 For 60-200 watt GLS lamp, BC cap.

Z5671 For 80-125 watt MBF/U lamp. 3/BC cap.

Z5672 For 60-200 watt GLS 80-125 watt MBF/U or 70-120 watt SON lamp, ES cap.

Z5678 35 watt Super SOX sodium lamp, BC cap.

Z5679 For 80-125 watt MBF/U lamp 3/BC cap but no dome refractor.

Z5679HPS For 50-70-120 watt SON lamp, ES cap but no dome refractor.

Made in U.K. Lanterns are packed in pairs.