



# Z5673/4/5NU Z5676/7

## Lanterns for Group B Lighting

Group B roadlighting lanterns with a cast aluminium post top mounting spigot cap. Top canopy moulded in DMC glass reinforced polyester. Non-axial dome refractor optical system with an injection moulded anti-vandal UV stabilised polycarbonate enclosing cone.

### APPLICATIONS

The lantern is suitable for:

- Group B roadlighting
- All forms of amenity lighting
- Precinct lighting
- Decorative lighting

### FEATURES

- Cast aluminium spigot cap.
- DMC glass reinforced polyester top canopy
- Injection moulded anti-vandal U.V. stabilised polycarbonate cone
- Non-axial asymmetric dome refractor

### MATERIALS AND FINISH

**Canopy:** DMC glass reinforced polyester

**Enclosing cone:** Anti-vandal U.V. stabilised polycarbonate.

**Dome refractor:** Glass.

**Spigot cap:** Cast aluminium for 76mm dia. x 76mm high spigot.

**Finish:** Canopy, light grey. Spigot, silver.



### LANTERN WEIGHTS AND WINDAGE DATA

Lantern Weight : Z5673/7	6.4 kg	Lantern Windage Area	0.116m <sup>2</sup>
--------------------------	--------	----------------------	---------------------

### ORDERING DATA

Z5673 For 60-200 watt GLS lamp, BC cap.

Z5674 For 80-125 watt MBF/U lamp. 3/BC cap.

Z5675 For 60-200 watt GLS 80-125 watt MBF/U or 70-120 watt SON lamp, ES cap.

Z5676 For 35-55 watt sodium lamp, BC cap.

Z5677 For 80-125 watt MBF/U lamp 3/BC cap but no dome refractor.

Z5677HPS For 50-70-120 watt SON lamp, ES cap but no dome refractor.

Made in U.K.      Lanterns are packed in pairs.