



Z5713/4/5U & Z5718/9U

Lanterns for Group B Road Lighting

Group B roadlighting lanterns with a cast aluminium post top mounting spigot cap. Spun aluminium top canopy. Vandal resistant polycarbonate long or short cone dependent on the lamp used which can be GLS, MBF/U, Super SOX or SON.



APPLICATIONS

The lantern is suitable for:

- Group B roadlighting
- All forms of amenity lighting
- Precinct lighting
- Decorative lighting

FEATURES

- Cast aluminium spigot cap
- Spun aluminium hinged top canopy
- Injection moulded anti-vandal U.V. stabilised polycarbonate cone

MATERIALS AND FINISH

Canopy: Spun aluminium.
Enclosing cone: Anti-vandal U.V. stabilised polycarbonate.
Spigot cap: Cast aluminium for 76mm dia. x 76mm high spigot.
Finish: Stove enamelled black.

LANTERN WEIGHTS AND WINDAGE DATA

Lantern Weight : Z5713/4/5U	2.7 kg	Lantern Windage Area	0.092 sq.m
Lantern Weight : Z5718/9U	3.7 kg	Lantern Windage Area	0.133 sq. m

ORDERING DATA

Z5713U for use with 60-200 watt GLS lamp or 35 watt Super SOX lamp. B.C. cap.
Z5714U for use with 80-125 watt Truelite MBF/U lamp 3/B.C. cap.
Z5715U for use with 80-125 watt Truelite MBF/U lamp or
50-70-120 watt Solarcolour SON lamp. E.S. cap.
Z5718U for use with 35-55 watt Super SOX lamp. B.C. cap.
Z5719U for use with 80-125 watt Truelite MBF/U lamp 3/B.C. cap.
The Z5713/4/5U lanterns have a short 279mm cone and the Z5718/9 a long 406mm cone.

Made in U.K. Lanterns are packed in pairs.