



### Technical Summary

<b>TYPE</b>	FULLY ELECTRONIC SOLID STATE
<b>SENSOR</b>	CDS
<b>VOLTAGE</b>	198 to 264V 50Hz
<b>SWITCH ON LEVEL</b>	70 LUX
<b>SWITCHING DIFF</b>	1:0.5 NEG · 1:1.5 POS · 1:3 OPTION
<b>TYPICAL LOAD</b>	70W
<b>OPERATING TEMP</b>	-20°C to +75°C
<b>MAX SWITCHING CAPACITY</b>	0.625A or 10µF (Subject to Derating at Higher Temperatures)
<b>SWITCHING DELAY</b>	15 SECONDS APPROX
<b>ENCLOSURE MATERIAL</b>	POLYCARBONATE
<b>POWER CONSUMPTION</b>	<0.5W
<b>STUD LENGTH</b>	<b>SS10</b> 10mm <b>SS11</b> 20mm
<b>APPROVALS</b>	EN 50081-1 EMISSIONS EN 50082-1 IMMUNITY
<b>IP RATING</b>	IP65 (INSTALLED)

### Electronic Miniature - SS10/SS11

**Increased Life:**

- Long-life components.

**Energy Saving:**

- 0.5W power consumption.

**Reduced Burning Hours:**


- Superior grade sensor utilised.

**Ease of Fitting:**

- Small case size and remote sensor option.

**Peace of Mind:**

- Cableform proven reliability and performance.



## ZODION™ Photocells

Cableform Ltd · Gratrix Lane · Sowerby Bridge · West Yorkshire HX6 2PH

Tel: +44 (0) 1422 833 533 · Fax: +44 (0) 1422 836 103

Email: sales@cableform.co.uk

www.cableform.co.uk

