




**Technical Summary**

<b>TYPE</b>	FULLY ELECTRONIC SOLID STATE
<b>SENSOR</b>	<b>SS5B</b> CdS HERMETICALLY SEALED <b>SS5C</b> CdS OPEN AND SEALED
<b>VOLTAGE</b>	198 to 264V 50Hz
<b>SWITCH ON LEVEL</b>	70 LUX
<b>SWITCHING DIFF</b>	1:0.5 NEG
<b>TYPICAL LOAD</b>	2 x 250 W
<b>OPERATING TEMP</b>	-20°C to +70°C
<b>MAX SWITCHING CAPACITY</b>	5A or 60µF
<b>SWITCHING DELAY</b>	15 SECONDS APPROX
<b>ENCLOSURE MATERIAL</b>	POLYCARBONATE
<b>POWER CONSUMPTION</b>	<0.25W
<b>APPROVALS</b>	EN 50081-1 EMISSIONS EN 50082-1 IMMUNITY
<b>IP RATING</b>	IP65

**Electronic - SS5B (shown) / SS5C**

- Long Life:**
- Superior quality components used throughout.
- Energy Saving:**
- 0.25W power consumption.
- Reduced Burning Hours:**
- High grade sensor utilised.
- Peace of Mind:**
- Cableform proven reliability and performance.



**ZODION™ Photocells**

5/03

Cableform Ltd · Gratrix Lane · Sowerby Bridge · West Yorkshire HX6 2PH  
Tel: +44 (0) 1422 833 533 · Fax: +44 (0) 1422 836 103  
Email: sales@cableform.co.uk



www.cableform.co.uk